



(Photo is just for reference)

### 24F Rack Mount fiber Shelf SCPC DX SM

#### Scope of supply:

- |                         |       |
|-------------------------|-------|
| • 19" 1U FMS            | 1 pc  |
| • SC-PC DX Adapters SM  | 12 pc |
| • Splice Trays          | 1 pc  |
| • 19" 1U Rack mount set | 1 pc  |
| • Kit 'B'               | 1 pcs |
| • Test Reports          |       |
| • Instruction Manual    |       |

| Description                                                        | PU       | Product-No.    |
|--------------------------------------------------------------------|----------|----------------|
| <b>19" 1U Rack Mount Fiber Shelf loaded with SC-PC DX SM - 24F</b> | <b>1</b> | <b>R220040</b> |

### Product description

The 19" 1U Fiber Shelf is a shelf assembly for a fiber management system in a networking rack environment. This system utilizes the same proven fiber routing procedures. The result is consistent, high quality fiber management throughout the network.

### Features

- Easy removable Top plate with push buttons
- Inner tray of patch panel can be easily slide front & back
- Splice elements for up to 12x SC-PC DX SM adapters
- Stress free and easy to handle fiber guidance
- High degree of flexibility and modularity
- Fast, secure and time saving installation and fiber routing
- Modular and flexible for splicing & patching applications

### Technical Data

| Criteria               |                                   | Date / Value                                    |
|------------------------|-----------------------------------|-------------------------------------------------|
| 1U Patch panel         | Material<br>Color                 | CRCA 1.2mm, powder coated<br>RAL 7035           |
| Splice Tray            | Material<br>Color                 | Plastic, ABS/PC                                 |
| Weight [kgs]           | net<br>Packed                     | 4.5<br>5.0                                      |
| Dimensions [mm]        | W x D x H                         | 482 x 270 x 44.5                                |
| Temperature range [°C] | Transport<br>Storage<br>Operation | -40 up to +85<br>-40 up to +85<br>-25 up to +55 |

### Standards

| Description                      | Standard                        |
|----------------------------------|---------------------------------|
| Climate testing                  | IEC 60068-2-2 / IEC 60068-2-1   |
| Temperature change and damp heat | IEC 61300-2-22 / IEC 61300-2-19 |